



Security With Visibility



Elegance In Merchandising



3

PROTECT your assets and optimize space

2

SHIELD your products while providing visibility

1

SECURE your retail premises 24/7

Retail Security Closures

OPERATION

- Control effortlessly by paddle switch or key switch
- Commercial-grade construction; requires little maintenance
- The curtain stores in a compact coil, saving valuable space
- Engineered and tested to meet and exceed industry standards
- Operation by jackshaft motor (customer supplied or included)
- Emergency egress and battery backup options


MATERIALS

- Provides excellent visibility, airflow, and security
- EntrexGuard offers a clean, uncluttered view that helps promote your business even when closed
- Commercial-grade aluminum - Environmentally friendly material with positive effects during production and operation
- Adds beauty to the interior and exterior of a building or storefront, with many different design configurations



BOTTOM BAR OPTIONS

- 75 mm (3 in) or 100 mm (4 in) Heavy Duty Bottom Bar
- 75 mm (3 in) or 150 mm (6 in) bottom bar plates available
- Bottom bar plates cover the ceiling opening when the curtain is coiled up in the open position



FRAME & CURTAIN COLOR OPTIONS

- Not all series are available in all colors; contact your dealer for options
- Additional charge for dark bronze, black, and custom colors



Arctic White



Clear Anodized



Aluminum Grey



Dark Bronze



Black



Custom Colors

SMALL PERFORATION



LARGE PERFORATION



CLEAR CURTAIN



BRICK PATTERN



STRAIGHT PATTERN



WINDOW OPENING



SHUTTER CURTAIN STYLES AND SIZING

Pentagon EntrexGuard curtain styles are finished in industry-leading coatings and provide options for visibility. Our engineered slats offer enhanced security and add to the visual appeal of your facility.



**530
Series**



**535
Series**



**560
Series**



**561
Series**



**562
Series**

SOLID CURTAIN

Description	560
The EntrexGuard 560 series solid curtain provides a highly secure barrier as a retail security closure system. It is strong and durable, allowing it to stand up against vandalism and intruders while not allowing light or air transfer. The 560 series provides optimum security and still looks amazing due to the smooth and sleek design of the curtain.	Single wall extruded aluminum

PERFORATED CURTAIN

Description	561	562
The perforated curtain is available in both the 561 and the 562 series. The perforated curtain allows light transfer through the shutter curtain and optimal airflow. The small perforation option is designed to provide an unobstructed view through the shutter. The large perforation option gives you the look of a "link and rod" grille door, with the advantage of having minimal moving parts.	Single wall extruded aluminum with small perforations	Single wall extruded aluminum with large perforations

PATTERNED CURTAIN

Description	530	535
The patterned curtain is available using the 530 and 535 series in EntrexGuard. Clear anodized connector rods are used between each slat. Curtain patterns we offer include clear, brick, straight, and window.	Clear polycarbonate / aluminum with curved design	Clear polycarbonate / aluminum with straight design

BOTTOM BAR SIZING

Description	HD Bottom Bar	Bottom Bar Plates
The EntrexGuard system is compatible with the Heavy Duty Bottom Bar (two sizes). These bottom bars are compatible with our EntrexGuard bottom bar plates to cover the ceiling opening.	3 in (75 mm) 4 in (100 mm)	3 in (75 mm) 6 in (150 mm)

GUIDE RAIL SIZING

Description	64 mm	83 mm	83 mm - AnchorLoc
Two guide rail sizes are compatible with the EntrexGuard system. AnchorLoc provides the ultimate strength and stability, with end retention securing the curtain to each guide rail.	2.5 in (64 mm)	3.25 in (83 mm)	3.25 in (83 mm)

SHUTTER AND CURTAIN SIZING

Series	Guide Rail Sizes	Bottom Bar Sizes	Maximum Curtain Height	Maximum Curtain Width	Maximum Curtain Area
530	64 mm, 83 mm, 83 mm - AnchorLoc	HD 3 in (75 mm), HD 4 in (100 mm)	Up to 192 in (4876 mm)	Up to 228 in (5791 mm)	208 sq. ft (19.4 sq. m)
535	64 mm, 83 mm, 83 mm - AnchorLoc	HD 3 in (75 mm), HD 4 in (100 mm)	Up to 192 in (4876 mm)	Up to 228 in (5791 mm)	208 sq. ft (19.4 sq. m)
560	64 mm, 83 mm, 83 mm - AnchorLoc	HD 3 in (75 mm), HD 4 in (100 mm)	Up to 192 in (4876 mm)	Up to 228 in (5791 mm)	284 sq. ft (26.4 sq. m)
561	64 mm, 83 mm, 83 mm - AnchorLoc	HD 3 in (75 mm), HD 4 in (100 mm)	Up to 192 in (4876 mm)	Up to 228 in (5791 mm)	284 sq. ft (26.4 sq. m)
562	64 mm, 83 mm, 83 mm - AnchorLoc	HD 3 in (75 mm), HD 4 in (100 mm)	Up to 192 in (4876 mm)	Up to 228 in (5791 mm)	284 sq. ft (26.4 sq. m)